

## Model

i.Series® PF15i Platelet Agitator

## Specifications

### Application, Rating and Electrical Data

Application	Provides continuous gentle agitation conditions required for the storage of platelet products
Storage Capacity	15 Random Bags / 5 Apheresis Bags
Incubator Compatibility	PC100i / PC100h
Electrical Power	100V 50/60Hz 115V 50/60Hz 230V 50/60Hz
Fuses	0.5A (100V and 115V, quantity 1) 0.3A (230V, quantity 2)
Maximum Current	0.4 FLA / 0.4 FLA / 0.25 FLA
Building Supply Rating	15 amp dedicated ground circuit
Certification / Agency Listing	QPS (Certified to UL and CSA Standards)
Indoor/Outdoor Use	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive, 5°C to 35°C (41°F to 95°F)

### Warranty

Standard (US/Canada)	2 years parts, 1 year labor
Outside US/Canada	Consult your local representative

### Dimensions and Construction

Exterior (w x h x d) in (mm)	15.25 x 12.5 x 9.25 / (387 x 318 x 235)
Base Material	Galvannealed steel with bacteria-resistant powder coating
Shelves	5 Stationary 1.5" (39mm) between shelves
Shelf Material	Galvannealed steel - perforated and powder coated
Motion Alarm	Standard - adjustable volume and delay
Motor	Heavy-duty, ball-bearing, gear
Fan	Single
Resin Glides	Yes
Net Weight	26.5 lb (12 kg)
Shipping Weight	32 lb (15 kg)
Clearance Requirements	Minimum 1" (25mm) across sides and 0.5" (13mm) across front and back for unobstructed movement and ventilation (when installed in a corresponding Helmer platelet incubator). Minimum 2" (50mm) across sides and 0.5" (13mm) across front and back for unobstructed movement and ventilation (when installed in a stand-alone configuration).
Options / Accessories	Red Designated Drawer, Extended Warranty



