

## Model

Horizon Series™ PC4200h Upright Platelet Incubator

## Specifications


Application, Rating and Elect	rical Data
Application	Provides the controlled temperature environment and continuous, gentle agitation required for the storage of platelet products
Storage Capacity	396 Random Bags/ 132 Apheresis Bags
Temperature Control Range	20° to 35°C
Electrical Power	115V 50/60Hz 230V 50/60Hz
Maximum Current	115V 14.5 FLA 230V 8.3 FLA
Building Supply Rating	20 amp dedicated ground circuit   115V 15 amp dedicated ground circuit   230V
Power Plug	NEMA 5-20 (115V) CEE7-7 (230V 50 Hz) NEMA 6-15 (230V 60Hz)
Agitation Speed (cycles/minute) Agitation speed is ±10% of nominal speed	60 (115V) 60 (230V 50 Hz) 72 (230V 60 Hz)
Certification / Agency Listing	QPS (Certified to UL and CSA Standards)
Indoor/Outdoor Use	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive, 15°C to 35°C (59°F to 95°F)
Refrigeration System	
Refrigeration System	Forced-air circulation
Compressor	1.9 HP (115V) 2.3 HP (230V)
Refrigerant Charge	R134A Non-CFC
Performance Data	
Uniformity	+/-1°C
Warranty	
Standard (US/Canada)	3 years compressor, 2 years parts, 1 year labor
Outside US/Canada	Consult your local representative


Controller	
Interface	LED digital display
Power Switch	On/Off - All Circuit breaker - 230V only
Controller Type	Digital microprocessor
High / Low Alarms	Fully adjustable
Power Failure Alarm	Yes
Battery Back-up	Yes
Dimensions and Construction	
Interior (w x h x d)	36.5 x 50.75 x 18 in 928 x 1290 x 458 mm
Exterior (w x h x d)	40.25 x 75.5 x 28 in 1023 x 1918 x 712 mm
Overall Exterior (w x h x d) (Includes door handle)	40.25 x 75.5 x 30.25 in 1023 x 1918 x 768 mm
Insulation	1" (26mm)
Exterior / Interior Finish	Bacteria-resistant powder coating
Doors	Dual-pane tempered glass
Key Lock	Yes
Auto-Stop/Start	Yes
Chart Recorder	Yes
Casters	Standard / swivel locking
Net Weight	667 lb (302 kg)
Shipping Weight	785 lb (356 kg)
Clearance Requirements	Minimum 4" (102mm) across sides and back for ventilation and power cord
Options / Accessories	Remote Alarms, Extended Warranty














Helmer Scientific | 14400 Bergen Boulevard | Noblesville, IN 46060 | USA +1.317.773.9073 | www.helmerinc.com

