

Model

Horizon Series™ PC3200h Floor Model Platelet Incubator

Specifications

Application, Rating and Electrical Data	
Application	Provides the controlled temperature environment required for the storage of platelet products
Agitator Capacity	3 PF96i or PF96h
Temperature Control Range	20° to 35°C
Electrical Power	115V 50/60Hz 230V 50/60Hz
Fuses	10.0A (230V, quantity 2)
Maximum Current	12 FLA / 7.0 FLA
Building Supply Rating	15 amp dedicated ground circuit
Certification / Agency Listing	QPS (Certified to UL and CSA Standards)
Indoor/Outdoor Use	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive, 15°C to 35°C (59°F to 95°F)
Refrigeration System	
Refrigeration System	Forced-air circulation
Compressor	1.8 HP (115V) 2.2 HP (230V)
Refrigerant Charge	R134A Non-CFC
Performance Data	
Uniformity	+/-1°C
Warranty	
Standard (US/Canada)	3 years compressor, 2 years parts, 1 year labor
Outside US/Canada	Consult your local representative

Controller	
Interface	LED digital display
Power Switch	On/Off - All Circuit breaker - 230V only
Controller Type	Digital microprocessor
High / Low Alarms	Fully adjustable
Power Failure Alarm	Yes
Battery Back-up	Yes
Dimensions and Construction	
Interior (w x h x d)	36.5 x 50.75 x 18 in 928 x 1290 x 458 mm
Exterior (w x h x d)	40.25 x 75.5 x 28 in 1023 x 1918 x 712 mm
Overall Exterior (w x h x d) (Includes door handle)	40.25 x 75.5 x 30.25 in 1023 x 1918 x 768 mm
Insulation	1" (26mm)
Exterior / Interior Finish	Bacteria-resistant powder coating
Doors	Dual-pane tempered glass
Key Lock	Yes
Auto-Stop/Start	Yes
Chart Recorder	Yes
Casters	Standard / swivel locking
Net Weight	477 lb (218 kg) 115V
	492 lb (224 kg) 230V
Shipping Weight	593 lb (270 kg) 115V
	608 lb (276 kg) 230V
Clearance Requirements	Minimum 4" (102mm) across sides and back for ventilation and power cord
Options / Accessories	Remote Alarms, Extended Warranty










Platelet Incubator









Helmer Scientific | 14400 Bergen Boulevard | Noblesville, IN 46060 | USA +1.317.773.9073 | www.helmerinc.com

